

Comprehensive Timely Monitoring, Intelligent Multiple Purification Modes Switch

Original function of "Pure L""Pure M""Pure H", 30mins quick deeply clean

Timely display of CO₂, temperature and humidity

Manual/Auto/Timer mode optional

Remote controller for easy function switch






Under mode "Auto", the ERV will adjust supply air volume according to indoor CO₂ range, corresponding speed as below:

CO ₂ Value	Status	Operational Speed
CO ₂ ≤500	Excellent	1
500 <co<sub>2≤650</co<sub>	Good	3
650 <co<sub>2≤800</co<sub>	Gentle Pollution	5
CO ₂ >800	Serious Pollution	8

Remark: To ensure sufficient indoor fresh air supply, the speed will rise automatically after model "Auto" runs for some time, 5-10 minutes later it will return to previous speed. During this time, the screen shows different speed from above chart.

CROSSFLOW HEAT EXCHANGER





Multiple Filtration for More Defense

- Pure physical purification, offers more safety and trust
 - Effectively isolates risk from ozone and high voltage electricity
- Four-layer filtration, up to H10 filtration class
 - PM2.5 purification effectiveness up to 99.9%



Technical Parameters

Model		ERVQ-B150-1A1F
Airflow	m³/h	150
Filtration efficiency	%	99% HEPA
Filtration mode		Pure High, Pure Medium, Pure Low
Speed		DC / 8 speed
Input power	W	35
Temperture efficiency	%	82 %
Noise	dB(A)	23 - 36
Control		Touch screen panel / Remote control
Air quality display		CO ₂ / Temp & R.H
Operational Mode		Manual / Auto / Timer
Suitable room size	m ²	20 - 45
Dimension	mm	450*155*660
Weight	kg	10
Weight	kg	10

Tel: +86-400-628-2002



